

Components should be blended using a mechanical stirrer. An agitator equipped pot should be utilized during application to prevent settling of heavy zinc pigment.

Caution: For spray application suitable protective vapor/particulate respirators should be worn by all personnel in the area. In poorly ventilated enclosed areas, a fresh air supplied mask should be worn. In all cases, observe OSHA regulations for respirator use (29 CFR 1910.134) whenever a respirator is used. It is important the spray droplets of paint not be inhaled.

IMPORTANT: Clean equipment immediately after use. In coating is allowed to harden on equipment, an industrial paint stripper is required to remove it.

PRECAUTIONS

Contains aromatic polyisocyanate prepolymer. Use adequate ventilation. In confined areas, use adequate forced ventilation during application and drying. When spraying suitable protective vapor/particulate respirator should be worn. In areas where there is a minimum of air movement a fresh air mask should be used. Observe OSHA regulations for respirator use (29 CFR 1910.134). **HARMFUL OR FATAL IF SWALLOWED.** If swallowed do not induce vomiting. Call physician immediately.

LIMITED WARRANTY : All statements, technical information and recommendations contained herein are based on tests the manufacturer believes to be reliable, but the accuracy or completeness thereof is not guaranteed, and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product proved to be defective at the time the sealed container is first opened, and in no event beyond the shelf date printed on the label. Neither seller, nor manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use of or the inability to use the product. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. All data, statements and recommendations made herein are based upon information manufacturer believes to be reliable, but are made without any representation or guarantee or warranty of accuracy and are made with reservation of all patent rights. All products are sold on the condition that the user will evaluate them, as well as manufacturer's recommendation, to determine their suitability for user's own purpose before adoption. Statements regarding the use of the products or processes are not to be construed as recommendations for their use in violation of any patent rights or in violation of any applicable laws or regulations.

Eye Irritant. Wear eye protection. In case of contact with eyes, flush repeatedly with water and contact a physician.

Difficult to Remove From Skin. Wear gloves and protective clothing. Moisture in skin will cause rapid cure. Do not attempt to remove cured coating on skin with solvent; soak in warm, soapy water. Barrier creams are not recommended where possible to cover with protective clothing.

COMBUSTIBLE. Keep away from heat, sparks and open flame. Refer also to package label and product material safety data sheet for additional safety and industrial hygiene information