

Alseal 521

1	PRODUCT AND COMPANY IDENTIFICATION		
Product Identifier:	Alseal 521		
Common Name:	Aluminum Filled Phosphate/Chromate solution		
SDS Number:	A9		
Revision Date:	5/6/2015		
Version:	1		
Chemical Family:	Acid		
Supplier Details:	Coatings for Industry, Inc. 319 Township Line Road Souderton, PA 18964		
Contact:	USA: 1-800-535-5053 / International :352-323-3500		
Phone:	215-723-0919		
Fax:	215-723-0911		
Email:	cs@cficoatings.com		
Web:	www.cficoatings.com		

HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

Health, Serious Eye Damage/Eye Irritation, 1 Health, Specific target organ toxicity - Repeated exposure, 1 Health, Carcinogenicity, 1 A Health, Germ cell mutagenicity, 1 B Health, Respiratory or skin sensitization, 1 Respiratory Environmental, Hazards to the aquatic environment - Acute, 1 Environmental, Hazards to the aquatic environment - Chronic, 1 Health, Respiratory or skin sensitization, 1 Skin Health, Reproductive toxicity, 2 Health, Acute toxicity, 4 Oral Health, Acute toxicity, 5 Dermal Health, Acute toxicity, 5 Inhalation

GHS Label elements, including precautionary statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:

2



GHS Hazard Statements:

- H318 Causes serious eye damage
- H372 Causes damage to organs through prolonged or repeated exposure
- H350 May cause cancer
- H340 May cause genetic defects
- H334 May cause allergy or asthma symptoms of breathing difficulties if inhaled
- H400 Very toxic to aquatic life
- H410 Very toxic to aquatic life with long lasting effects
- H317 May cause an allergic skin reaction
- H361 Suspected of damaging fertility or the unborn child
- H302 Harmful if swallowed
- H313 May be harmful in contact with skin



Alseal 521

H333 - May be harmful if inhaled

GHS Precautionary Statements:

P201 - Obtain special instructions before use.

P220 - Keep/Store away from clothing/combustible materials.

P234 - Keep only in original container.

P260 - Do not breathe dust/fume/gas/mist/vapors/spray.

P264 - Wash hands thoroughly after handling.

P273 - Avoid release to the environment.

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P284 - Wear respiratory protection.

P301+330+331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

SDS

P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.

P310 - Immediately call a POISON CENTER or doctor/physician.

P363 - Discard contaminated clothing or wash before reuse.

P390 - Absorb spillage to prevent material damage.

P501 - Dispose of contents/container to licensed hazardous waste disposal service.

3

COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas# % Chemical Name

7732-18-5 37-46% Water 92203-02-6 14-18% Phosphoric acid, reaction products with aluminum hydroxide and chromium oxide (CrO3) 7429-90-5 40-45% Aluminum powder, uncoated *2.9-3.5% of total weight is Cr03.......PEL-.005 mg/m3 ceiling for Cr0₃ ACGIH-as soluble Cr (VI) compound

0.05 mg/m3 NIOSH - as Cr (VI) compound 0.001 mg/m3 10 hour TWA

4		FIRST AID MEASURES
Inhalation:	•	nptoms develop, move victim to fresh air. If symptoms persist, obtain medical attention. Give oxygen or artificail iration if needed. Get immediate medical attention.
Skin Contact:	deco	ove contaminated clothing and footwaer and wash before reuse. Discard clothing and footwear which cannot be ontaminated. h with soap and water for at least 15 minutes. Get medical attention if needed or irritaion develops.
Eye Contact:	lmm irriga Was	ediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate ation. hing eyes within one minute is essential to achieve maximum effectiveness.
Ingestion:	avail	er give anything by mouth to an unconscious person. Do NOT induce vomiting. Drink large quantities of water. If able, give several galsses of milk. Follow with milk of magnesia. If vomiting occurs spontaneously, keep airway r and give more water. Seek immediate medical attention



Alseal 521

FIRE FIGHTING MEASURES

Flammability:	Non-Flammable
Flash Point:	N/A
LEL:	N/A
UEL:	N/A
Extinguishing Media	

Use Sand or Carbon Dioxide (CO2)

Extinguishing Media:

5

6

Use Sand or Carbon Dioxide (CO₂)

Special Fire Fighting Procedures:

Wear protective clothing and NIOSH/OSHA approved positive pressure self contained breathing apparatus in fire conditions. Do not use extinguishing agents containing water as a reaction with aluminum may produce hydrogen gas. **Unusual Fire or Explosion Hazards:**

Contact with alkalis, strong reducing or oxidizing agents may produce hydrogen gas causing fire or explosion hazard.Caution: Toxic phosphide may be given off in fire or other very high temperature conditions.

ACCIDENTAL RELEASE MEASURES

Evacuate nonessential personnel. Avoid contact with eyes.

Do not discharge into drains.

Use sawdust, vermiculite, Fuller's Earth or other absorbent material to soak up spill then neutralize with sodium bicarbonate. Then flush area with water. Do not use strong alkalis.

Waste Disposal Method:

Filter to remove solids and discard as solid chemical waste. Treat remaining liquid with sodium metabisulfate, then precipitate trivalent chromium by neutralizing with alkali, such as lime. Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

7	HANDLING AND STORAGE	
Handling Precautions:	Avoid breathing vapors or mist. Avoid contact with eyes, skin, or clothing. Launder contaminated clothing. Wash clothing before reuse and decontaminate or discard contaminated shoes. Wash thoroughly after handling.	
	Employee education and training in the safe use and handling of this product is required under the OSHA Hazard Communication Standard.	
Storage Requirements:	Store in area where it will not come into contact with strong alkalis or oxidizing agents. Protect form freezing.	
8	EXPOSURE CONTROLS/PERSONAL PROTECTION	
Engineering Controls:	All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94).	
Personal Protective Personal protective equipment		
Equipment:	Eye/face protection: Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye	

SDS

Coatings for Industry, Inc.

Alseal 521

protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure: Do not let product enter drains.

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Full contact Material: Nitrile rubber Minimum layer thickness: 0.11 mm Break through time: 480 min Material tested:Dermatril (KCL 740 / Aldrich Z677272, Size M) Splash contact data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Skin and body protection: Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures: Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

Components with workplace control parameters

Aluminum powder, uncoated (7429-90-5)

7429-90-5 TWA 1 mg/m3 USA. ACGIH Threshold Limit Values (TLV) Lower Respiratory Tract irritation Pneumoconiosis Neurotoxicity Not classifiable as a human carcinogen

TWA TWA	15 mg/m3 5 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants
TWA	15 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
TWA	5 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
TWA	5 mg/m3	USA. NIOSH Recommended Exposure Limits
TWA	10 mg/m3	USA. NIOSH Recommended Exposure Limits

Phosphoric acid (7664-38-2)

TWA	1 mg/m3	USA. ACGIH Threshold Limit Values (TLV)
STEL	3 ppm	USA. ACGIH Threshold Limit Values (TLV)

Eye, skin, & Upper Respiratory Tract irritation

TWA	1 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
TWA	1 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
STEL	3 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000



Alseal 521

TWA	1 mg/m3	USA. NIOSH Recommended Exposure Limits
ST	3 mg/m3	USA. NIOSH Recommended Exposure Limits

Chromium oxide (CrO3) (1333-82-0)

TWA 0.001 mg/m3 USA. NIOSH Recommended Exposure Limits

Potential Occupational Carcinogen See Appendix C See Appendix A See Table Z-2 for the exposure limit for any operations or sectors where the exposure limit in

1910.1026 is stayed or is otherwise not in effect Substance listed; for more information see OSHA document 1910.1026

See 1910.1026. See Table Z-2 for the exposure limit for any operations or sectors where the exposure limit in 1910.1026 is stayed or are otherwise not in effect.

Aluminum hydroxide (AI(OH)3) (21645-51-2) : no data available

9	PHYSICAL AND CHEMICAL PROPERTIES		
Appearance: Physical State: Spec Grav./Density: Viscosity: Boiling Point: Flammability: pH:	Opaque green-gray Liquid 1.65 +/- 0.05 15-20 (#2 Zahn Cup) 212 F Non-Flammable 1.25 +/25	Odor: Solubility: Percent Volatile: Freezing/Melting Pt.: Flash Point: VOC:	No odor Soluble 67.5 +/- 2.5% (by volume) 32 F N/A 0%

STABILITY AND REACTIVITY

Stability:Product is stable under normal conditionsMaterials to Avoid:Alkalis, Strong Oxidizing Agents, Strong Reducing agents.Hazardous Decomposition:Not known.Hazardous Polymerization:Will not occur.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Aluminum powder, uncoated (7429-90-5)

Information on toxicological effects

Acute toxicity: Oral LD50 LD50 Oral - rat - > 2,000 mg/kg Inhalation LC50 LC50 Inhalation - rat - 4 h - > 888 mg/l Dermal LD50 no data available Other information on acute toxicity

Skin corrosion/irritation: no data available Serious eye damage/eye irritation: no data available Respiratory or skin sensitisation: no data available Germ cell mutagenicity: no data available

10

11



Alseal 521

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Cough, weight loss, anemia, Weakness, Incoordination.

Synergistic effects: no data available

Additional Information:

RTECS: BD0330000

Phosphoric acid (7664-38-2)

Information on toxicological effects

Acute toxicity:

Ingestion/Oral Rat LD50 1530mg/kg Inhalation: no data available Dermal: Skin-Rabbit LD50 2740mg/kg

Irritation:

Eye-Rabbit 119mg/kg Severe irritaion, irreversible burns (corrosive) Skin-Rabbit 595mg/kg 24 hours Severe irritaion, irreversible burns (corrosive) Note: Information above for Phosphoric Acid

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: Not available

burning sensation, Cough, wheezing, laryngitis, Shortness of breath, spasm, inflammation and edema of the larynx, spasm, inflammation



Alseal 521

and edema of the bronchi, pneumonitis, pulmonary edema, Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin. Stomach - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence (Phosphoric acid)

Chromium oxide (CrO3) (1333-82-0)

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50 Oral - rat - male and female - 52 mg/kg Inhalation LC50 LC50 Inhalation - rat - male - 4 h - 217 mg/m3 Dermal LD50 LD50 Dermal - rabbit - male and female - 57 mg/kg Other information on acute toxicity no data available

Skin corrosion/irritation: Skin - rabbit - Corrosive - 24 h

Serious eye damage/eye irritation: Eyes - rabbit - Corrosive to eyes

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: May alter genetic material. In vivo tests showed mutagenic effects

Carcinogenicity:

This is or contains a component that has been reported to be carcinogenic based on its IARC, OSHA, ACGIH, NTP, or EPA classification. Human carcinogen.

IARC: 1 - Group 1: Carcinogenic to humans (Chromium trioxide)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: Known to be human carcinogen (Chromium trioxide)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: May cause reproductive disorders.

Teratogenicity: Suspected human reproductive toxicant

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be fatal if inhaled. Material is extremely destructive to the tissue of the mucous membranes and upper respiratory tract. Ingestion Toxic if swallowed. Skin Toxic if absorbed through skin. Causes skin burns. Eyes Causes eye burns. Causes severe eye burns.

Signs and Symptoms of Exposure: Material is extremely destructive to tissue of the mucous membranes and upper respiratory tract, eyes, and skin., Cough, Shortness of breath, Headache, Nausea

Synergistic effects: no data available

Additional Information:

RTECS: GB6650000



SDS

Coatings for Industry, Inc.

Alseal 521

Information on toxicological effects

Acute toxicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: n o data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: Nausea, Vomiting, Constipation.

Synergistic effects: no data available

Additional Information: RTECS: BD0940000

12

ECOLOGICAL INFORMATION

Aluminum powder, uncoated (7429-90-5)

Information on ecological effects

Toxicity: LC50 0.16mg/l, 96hrs. (Rainbow trout, donaldson trout) Persistence and degradability: not biodegradeable Bioaccumulative potential: no data available Mobility in soil: no data available PBT and vPvB assessment: no data available

Other adverse effects: no data available

Phosphoric acid (7664-38-2)



SDS

Coatings for Industry, Inc.

Alseal 521

Information on ecological effects

Toxicity: Mosquitofish LC50 138mg/L 96 hours Persistence and degradability: no data available Bioaccumulative potential: no data available Mobility in soil: no data available Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Chromium oxide (CrO3) (1333-82-0)

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Tilapia mossambica - 21.05 - 141.38 mg/l - 96.0 h. LC0 - Leuciscus idus (Golden orfe) - 100 mg/l - 48.0 h Toxicity to daphnia EC50 - Daphnia magna (Water flea) - 0.8 mg/l - 48 h. and other aquatic invertebrates Persistence and degradability: no data available Bioaccumulative potential: no data available Mobility in soil: no data available PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Very toxic to aquatic life with long lasting effects.

13 DISPOSAL CONSIDERATIONS

Waste disposal method: Filter to remove aluminum and discard as solid chemical waste. Treat remaining liquid with sodium metabisulfate, then precipitate trivalent chromium by neutralizing with alkali, such as lime.

Waste must be disposed of in accordance with federal, state, and local environmental control regulations.

14 TRANSPORT INFORMATION

Non-hazardous for air, sea and road freight.



Alseal 521

15

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Phosphoric acid, reaction products with aluminum hydroxide and chromium oxide (CrO3) (92203-02-6) [14-18%] TSCA

Aluminum powder, uncoated (7429-90-5) [40-45%] EPCRAWPC, MASS, NJHS, OSHAWAC, PA, SARA313, TSCA, TXAIR

Chromium oxide (CrO3) (1333-82-0) [2.9-3.5%] MASS, PA, PROP65, SARA313, TSCA

Regulatory CODE Descriptions TSCA = Toxic Substances Control Act EPCRAWPC = EPCRA Water Priority Chemicals MASS = MA Massachusetts Hazardous Substances List NJHS = NJ Right-to-Know Hazardous Substances OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances SARA313 = SARA 313 Title III Toxic Chemicals TXAIR = TX Air Contaminants with Health Effects Screening Level PROP65 = CA Prop 65

16

OTHER INFORMATION

NOTICE: This information is presented in good faith and believed to be accurate as of the effective date below. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Coatings For Industry, Inc. assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material. Regulatory requirements are subject to change and may differ from one location to another: it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The preceding specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations.