

1	PRODUCT AND COMPANY IDENTIFICATION
Product Identifier: Common Name: SDS Number: Revision Date: Version:	U-498 Part A Epoxy resin I67 11/17/2015
Supplier Details:	Coatings For Industry, Inc. 319 Township Line Road Souderton, PA 18964
Emergency: Contact: Phone:	Infotrac USA: 1-800-535-5053 / International :352-323-3500 215-723-0019
Fax: Email: Web:	215-723-0911 cs@cficoatings.com www.cficoatings.com

2

HAZARDS IDENTIFICATION

Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):

Health, Reproductive toxicity, 1 B Health, Respiratory or skin sensitization, 1 Skin Health, Skin corrosion/irritation, 2 Health, Serious Eye Damage/Eye Irritation, 2 A Physical, Flammable Liquids, 3 Health, Specific target organ toxicity - Single exposure, 3 Health, Acute toxicity, 4 Dermal Health, Acute toxicity, 4 Inhalation Health, Acute toxicity, 5 Oral Environmental, Hazards to the aquatic environment - Chronic, 2

GHS Label elements, including precautionary statements

GHS Signal Word: DANGER

GHS Hazard Pictograms:



GHS Hazard Statements:

- H360 May damage fertility or the unborn child
- H317 May cause an allergic skin reaction
- H315 Causes skin irritation
- H319 Causes serious eye irritation
- H226 Flammable liquid and vapor
- H336 May cause drowsiness or dizziness
- H312 Harmful in contact with skin
- H332 Harmful if inhaled
- H303 May be harmful if swallowed
- H411 Toxic to aquatic life with long lasting effects

GHS Precautionary Statements:

P280 - Wear protective gloves/protective clothing/eye protection/face protection.

P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do.



Continue rinsing.

- P273 Avoid release to the environment.
- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking
- P264 Wash hands and skin thoroughly after handling.

COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients:

3

4

Cas#	%	Chemical Name
$\begin{array}{c} 1330-20-7\\ 25068-38-6\\ 763-69-9\\ 98-56-6\\ 108-65-6\\ 28064-14-4 \end{array}$	5-10% 15-25% 0-1% 16-19% 7-10% 1-5%	Xylene Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane Propanoic acid, 3-ethoxy-, ethyl ester Benzene, 1-chloro-4-(trifluoromethyl)- 2-Propanol, 1-methoxy-, acetate Phenol, polymer with formaldehyde, glycidyl ether

| FIRST AID MEASURES

Inhalation:	Remove to fresh air. If not breathing, give mouth to mouth resuscitation. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.
Skin Contact:	Wash off in flowing water or shower.
Eye Contact:	Irrigate immediately with water for at least 5 minutes. Seek medical attention.
Ingestion:	Do not induce vomiting. Call a physician and/or transport to emergency medical facility immediately.

5FIRE FIGHTING MEASURESFlash Point:80F (27C)Flash Point Method:PMCCLEL:1.1% based on XyleneUEL:7.0% based on Xylene

Extinguishing Media - Foam, Dry Chemical, Carbon Dioxide (CO2) Fire and Explosion Hazards - Presence of xylene requires grounding. Keep away from possible ignition sources. Fire Fighting Equipment - Wear positive pressure self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

If Material is Spilled - Soak up in absorbent material such as sand and collect in suitable containers. Residual resin may be removed using steam or hot soapy water. Solvents are not recommended for cleanup unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed. Consult appropriate solvent MSDS for handling information and exposure guidelines. Keep spark producing equipment away. For large spills, evacuate upwind of spills and contain with dike.

7 HANDLING AND STORAGE

Handling Precautions:	General Handling: Keep away from heat, sparks and flame. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor. Do not swallow. Keep container
	closed. Use with adequate ventilation. Wash thoroughly after handling. Never use air pressure for
	transferring product. No smoking, open flames or sources of ignition in handling and storage area.
	Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition
	and/or flash back may occur. Electrically bond and ground all containers and equipment before transfer
	or use of material. Containers, even those that have been emptied, can contain vapors. Do not cut, drill,
	grind, weld, or perform similar operations on or near empty containers.



		U-498 Part A
Storage Red	quirements	: Minimize sources of ignition, such as static build-up, heat, spark or flame. Store in original container. Keep container tightly closed.
8		EXPOSURE CONTROLS/PERSONAL PROTECTION
Engineering Controls: Personal Protective Equipment:		Provide general and/or local exhaust ventilation to control airborne levels below the TLV. Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).
		Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.
		Body Protection: impervious clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
		Eye protection: Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).
		Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.
Xylene (13	30-20-7) [5-10%]
Component	ts with wor	kplace control parameters
TWA 435	100 ppm 5 mg/m3	USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants
TWA 435	100 ppm 5 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
STEL 655	150 ppm 5 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000

TWA 100 ppm USA. ACGIH Threshold Limit Values (TLV) 434 mg/m3

Not classifiable as a human carcinogen

STEL 150 ppm USA. ACGIH Threshold Limit Values (TLV) 651 mg/m3

Not classifiable as a human carcinogen

TWA100 ppmUSA. ACGIH Threshold Limit Values (TLV)Eye & Upper Respiratory Tract irritation Central Nervous System impairment Substances for which
there is a Biological Exposure Index or Indices (see BEI section) Not classifiable as a human
carcinogen

STEL 150 ppm USA. ACGIH Threshold Limit Values (TLV) Eye & Upper Respiratory Tract irritation Central Nervous System impairment Substances for which there is a Biological Exposure Index or Indices (see BEI section) Not classifiable as a human carcinogen



TWA The va	100 ppm 435 mg/m3 lue in mg/m3 is appr	USA. Occupational Exposure Limits (OSHA) - Table Z- 1 Limits for Air Contaminants oximate.
TWA	100 ppm 435 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
STEL	150 ppm 655 mg/m3	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
Phenol	, 4,4'-(1-methylethyli	dene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%] : no data available
Propar	oic acid, 3-ethoxy-,	ethyl ester (763-69-9) [0-1%] : no data available

Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) [16-19%] : no data available

2-Propanol, 1-methoxy-, acetate (108-65-6) [7-10%]

Components with workplace control parameters

TWA 50 ppm USA. Workplace Environmental Exposure Levels (WEEL)

Phenol, polymer with formaldehyde, glycidyl ether (28064-14-4) [1-5%]: no data available

9 PHYSICAL AND CHEMICAL PROPERTIES Appearance: Gray Physical State: Viscous liquid Spec Grav./Density: 0dor: Solvent odor 1.3-1.45 Solubility: Negligible in water Percent Volatile: 30-40

STABILITY AND REACTIVITY

Chemical Stability:	This product is stable
Conditions to Avoid:	Xylene may produce excessive pressure when heated.
Materials to Avoid:	Bases
Hazardous Decomposition:	The by products expected in complete pyrolysis or combustion of epoxy resins are mainly phenolics, carbon monoxide and water. The thermal decomposition products of epoxy resins therefore should be treated as potentially hazardous substances, and appropriate precautions should be taken.
Hazardous Polymerization:	Will not occur by itself, but masses of more than one pound of product plus an aliphatic amine can cause irreversible polymerization with considerable heat buildup.

11

10

TOXICOLOGICAL INFORMATION

Xylene (1330-20-7) [5-10%]

Acute toxicity: Oral LD50 no data available Inhalation LC50



Dermal LD50 Other information on acute toxicity Skin corrosion/irritation: no data available Serious eye damage/eye irritation: Eyes: no data available Respiratory or skin sensitization: no data available Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: 2B - Group 2B: Possibly carcinogenic to humans (Ethylbenzene)

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Xylene)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available Teratogenicity: no data available Specific target organ toxicity - single exposure (Globally Harmonized System): no data available Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%]

Acute toxicity: Oral LD50 LD50 Oral - rat - 13,600 mg/kg Remarks: Behavioral:Somnolence (general depressed activity). Lungs, Thorax, or Respiration:Dyspnea. Nutritional and Gross Metabolic:Weight loss or decreased weight gain. Inhalation LC50 no data available Dermal LD50 Other information on acute toxicity Skin corrosion/irritation: no data available Serious eye damage/eye irritation: no data available Respiratory or skin sensitization: May cause sensitization by skin contact. Germ cell mutagenicity: no data available Genotoxicity in vitro - Ames test - positive

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available Teratogenicity: no data available Specific target organ toxicity - single exposure (Globally Harmonized System): no data available Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin

GHS Safety Data Sheet



U-498 Part A

May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Propanoic acid, 3-ethoxy-, ethyl ester (763-69-9) [0-1%]

Acute toxicity:

Oral LD50 LD50 Oral - rat - male - > 5,000 mg/kg LD50 Oral - rat - female - 4,309 mg/kg Inhalation LC50 LC50 Inhalation - rat - male - 6 h - > 998 ppm Dermal LD50 LD50 Dermal - rabbit - male - 4,080 mg/kg LD50 Dermal - rabbit - female - 4,680 mg/kg Other information on acute toxicity no data available

Skin corrosion/irritation: Skin - rabbit - No skin irritation - 4 h - OECD Test Guideline 404 Serious eye damage/eye irritation: Eyes - rabbit - No eye irritation - 24 h - OECD Test Guideline 405 Respiratory or skin sensitisation: guinea pig - Does not cause skin sensitisation. - OECD Test Guideline 406 Germ cell mutagenicity: Genotoxicity in vitro - S. typhimurium - with and without metabolic activation - negative

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):

no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Nausea, Headache, Vomiting, Central nervous system depression, Dizziness

Additional Information: Repeated dose toxicity - rat - male and female - Oral - No observed adverse effect level - 1,000 mg/kg RTECS: UF3325000

Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) [16-19%]

Acute toxicity: LD50 Oral - rat - 13,000 mg/kg Dermal: no data available

Skin corrosion/irritation: no data available Serious eye damage/eye irritation: no data available Respiratory or skin sensitisation: no data available Germ cell mutagenicity: Human Embryo Unscheduled DNA synthesis

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by



OSHA.

Reproductive toxicity: no data available Specific target organ toxicity - single exposure: Inhalation - May cause respiratory irritation. Specific target organ toxicity - repeated exposure: no data available To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

2-Propanol, 1-methoxy-, acetate (108-65-6) [7-10%]

Acute toxicity: Oral LD50 LD50 Oral - rat - 8,532 mg/kg Inhalation LC50 no data available Dermal LD50 LD50 Dermal - rabbit - > 5,000 mg/kg Other information on acute toxicity

Skin corrosion/irritation: Skin - rabbit - No skin irritation Serious eye damage/eye irritation: no data available Respiratory or skin sensitisation: Maximisation Test - guinea pig - Did not cause sensitisation on laboratory animals. Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: Specific target organ toxicity - single exposure (Globally Harmonized System):

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):

no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Phenol, polymer with formaldehyde, glycidyl ether (28064-14-4) [1-5%]

Information on toxicological effects

Acute toxicity: Oral LD50 no data available Inhalation LC50 no data available Dermal LD50 no data available

Other information on acute toxicity Skin corrosion/irritation: no data available Serious eye damage/eye irritation: no data available Respiratory or skin sensitisation: Prolonged or repeated exposure may cause allergic reactions in certain sensitive individuals. Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

GHS Safety Data Sheet



U-498 Part A

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Synergistic effects: no data available

Additional Information:

RTECS: Not available

12 ECOLOGICAL INFORMATION

Xylene (1330-20-7) [5-10%]

Toxic to aquatic life.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%]

Persistence and degradability: Biodegradability Result: - According to the results of tests of biodegradability this product is not readily biodegradable. Remarks: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects.

Propanoic acid, 3-ethoxy-, ethyl ester (763-69-9) [0-1%]

Toxicity:

Toxicity to fish static test LC50 - Pimephales promelas (fathead minnow) - 55.3 mg/l - 96 h. Method: OECD Test Guideline 203 static test LC50 - Pimephales promelas (fathead minnow) - 45.3 mg/l - 96 h Toxicity to daphnia Immobilization EC50 - Daphnia magna (Water flea) - > 479.7 mg/l - 48 h. and other aquatic Method: OECD Test Guideline 202 invertebrates Immobilization EC50 - Daphnia magna (Water flea) - 785 mg/l - 48 h Toxicity to algae Growth inhibition EC50 - Selenastrum capricornutum (green algae) - > 114.86 mg/l - 72 h. Method: OECD Test Guideline 201 Toxicity to bacteria Growth inhibition IC50 - other microorganisms - > 5,000 mg/l - 16 h. Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life.

2-Propanol, 1-methoxy-, acetate (108-65-6) [7-10%]

Toxicity: Toxicity to fish mortality LC50 - Salmo gairdneri - 100 - 180 mg/l - 96 h. Method: OECD Test Guideline 203 Toxicity to daphnia Immobilization EC50 - Daphnia magna (Water flea) - > 500 mg/l - 48 h.



and other aquatic Method: Tested according to Annex V of Directive 67/548/EEC. invertebrates Persistence and degradability: Biodegradability Biotic/Aerobic Result: 100 % - Readily biodegradable. Other adverse effects: Biochemical Oxygen 0.36 mg/l Demand (BOD) Chemical Oxygen 1.74 mg/g Demand (COD) An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Harmful to aquatic life. Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%] Information on ecological effects Toxicity: no data available Persistence and degradability: Biodegradability Result: - According to the results of tests of biodegradability this product is not readily biodegradable. Remarks: no data available Bioaccumulative potential: no data available Mobility in soil: no data available PBT and vPvB assessment: no data available Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life with long lasting effects. no data available Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) [16-19%] Information on ecological effects Toxicity: no data available Persistence and degradability: no data available Bioaccumulative potential: no data available Mobility in soil: no data available Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted Other adverse effects: no data available Phenol, polymer with formaldehyde, glycidyl ether (28064-14-4) [1-5%] Information on ecological effects Toxicity: no data available Persistence and degradability: no data available Bioaccumulative potential: no data available Mobility in soil: no data available PBT and vPvB assessment: no data available Other adverse effects: no data available 13 **DISPOSAL CONSIDERATIONS**

14 TRANSPORT INFORMATION

UN1263, Paint, 3, PGIII



ΙΑΤΑ

UN/ID No. : UN1263 Proper shipping name :Paint Class or Division : 3 Packing group : III Label(s) : 3 RQ Substance : Yes

IMDG

15

UN/ID No. : UN1263 Proper shipping name :Paint Class or Division : 3 Packing group : III Label(s) : 3 RQ Substance : Yes

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

RQ(100LBS), Xylene (1330-20-7) [5-10%] CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%] TSCA Propanoic acid, 3-ethoxy-, ethyl ester (763-69-9) [0-1%] TSCA Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) [16-19%] TSCA 2-Propanol, 1-methoxy-, acetate (108-65-6) [7-10%] TSCA Phenol, polymer with formaldehyde, glycidyl ether (28064-14-4) [1-5%] TSCA

Regulatory CODE Descriptions

RQ = Reportable Quantity CERCLA = Superfund clean up substance CSWHS = Clean Water Act Hazardous substances EPCRAWPC = EPCRA Water Priority Chemicals HAP = Hazardous Air Pollutants MASS = MA Massachusetts Hazardous Substances List NJHS = NJ Right-to-Know Hazardous Substances OSHAWAC = OSHA Workplace Air Contaminants PA = PA Right-To-Know List of Hazardous Substances SARA313 = SARA 313 Title III Toxic Chemicals TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List) TSCA = Toxic Substances Control Act TXAIR = TX Air Contaminants with Health Effects Screening Level TXHWL = TX Hazardous Waste List

16 OTHER INFORMATION

Notice - This information is presented in good faith and believed to be accurate as of the effective date below. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Coatings For Industry, Inc. assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material, such vendees or users assume all risks associated with the use of the material. Regulatory requirements are subject to change and may differ from one location to another: it is the buyer's responsibility to ensure that its activities comply with federal, state, and local laws. The preceding specific information is made for the purpose of complying with numerous federal, state, and local laws and regulations

