

Wearcoat 491 Part A

1	PRODUCT AND COMPANY IDENTIFICATION
----------	---

Product Identifier: Wearcoat 491 Part A
Common Name: Epoxy resin
SDS Number: I67
Revision Date: 11/17/2015
Version: 1
Supplier Details: Coatings For Industry, Inc.
 319 Township Line Road
 Souderton, PA 18964
Emergency: Infotrac
Contact: USA: 1-800-535-5053 / International :352-323-3500
Phone: 215-723-0919
Fax: 215-723-0911
Email: cs@cficoatings.com
Web: www.cficoatings.com

2	HAZARDS IDENTIFICATION
----------	-------------------------------

Classification of the substance or mixture**GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):**

Health, Reproductive toxicity, 1 B
 Health, Respiratory or skin sensitization, 1 Skin
 Health, Skin corrosion/irritation, 2
 Health, Serious Eye Damage/Eye Irritation, 2 A
 Physical, Flammable Liquids, 3
 Health, Specific target organ toxicity - Single exposure, 3
 Health, Acute toxicity, 4 Dermal
 Health, Acute toxicity, 4 Inhalation
 Health, Acute toxicity, 5 Oral
 Environmental, Hazards to the aquatic environment - Chronic, 2

GHS Label elements, including precautionary statements**GHS Signal Word:** DANGER**GHS Hazard Pictograms:****GHS Hazard Statements:**

H360 - May damage fertility or the unborn child
 H317 - May cause an allergic skin reaction
 H315 - Causes skin irritation
 H319 - Causes serious eye irritation
 H226 - Flammable liquid and vapor
 H336 - May cause drowsiness or dizziness
 H312 - Harmful in contact with skin
 H332 - Harmful if inhaled
 H303 - May be harmful if swallowed
 H411 - Toxic to aquatic life with long lasting effects

GHS Precautionary Statements:

P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P305+351+338 - IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do.

Wearcoat 491 Part A

Continue rinsing.
 P273 - Avoid release to the environment.
 P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
 P264 - Wash hands and skin thoroughly after handling.

3 COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas#	%	Chemical Name
1330-20-7	5-10%	xylene
25068-38-6	15-25%	Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane
763-69-9	0-1%	Propanoic acid, 3-ethoxy-, ethyl ester
98-56-6	16-19%	Benzene, 1-chloro-4-(trifluoromethyl)-
108-65-6	7-10%	2-Propanol, 1-methoxy-, acetate
28064-14-4	1-5%	Phenol, polymer with formaldehyde, glycidyl ether

4 FIRST AID MEASURES

Inhalation: Remove to fresh air. If not breathing, give mouth to mouth resuscitation. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

Skin Contact: Wash off in flowing water or shower.

Eye Contact: Irrigate immediately with water for at least 5 minutes. Seek medical attention.

Ingestion: Do not induce vomiting. Call a physician and/or transport to emergency medical facility immediately.

5 FIRE FIGHTING MEASURES

Flash Point: 80F (27C)
Flash Point Method: PMCC
LEL: 1.1% based on Xylene
UEL: 7.0% based on Xylene

Extinguishing Media - Foam, Dry Chemical, Carbon Dioxide (CO2)

Fire and Explosion Hazards - Presence of xylene requires grounding. Keep away from possible ignition sources.

Fire Fighting Equipment - Wear positive pressure self-contained breathing apparatus.

6 ACCIDENTAL RELEASE MEASURES

If Material is Spilled - Soak up in absorbent material such as sand and collect in suitable containers. Residual resin may be removed using steam or hot soapy water. Solvents are not recommended for cleanup unless the recommended exposure guidelines and safe handling practices for the specific solvent are followed. Consult appropriate solvent MSDS for handling information and exposure guidelines. Keep spark producing equipment away. For large spills, evacuate upwind of spills and contain with dike.

7 HANDLING AND STORAGE

Handling Precautions: General Handling: Keep away from heat, sparks and flame. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin, and clothing. Avoid breathing vapor. Do not swallow. Keep container closed. Use with adequate ventilation. Wash thoroughly after handling. Never use air pressure for transferring product. No smoking, open flames or sources of ignition in handling and storage area. Vapors are heavier than air and may travel a long distance and accumulate in low lying areas. Ignition and/or flash back may occur. Electrically bond and ground all containers and equipment before transfer or use of material. Containers, even those that have been emptied, can contain vapors. Do not cut, drill, grind, weld, or perform similar operations on or near empty containers.

Wearcoat 491 Part A

Storage Requirements: Minimize sources of ignition, such as static build-up, heat, spark or flame. Store in original container. Keep container tightly closed.

8	EXPOSURE CONTROLS/PERSONAL PROTECTION
----------	--

Engineering Controls: Provide general and/or local exhaust ventilation to control airborne levels below the TLV.

Personal Protective Equipment: Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Body Protection: impervious clothing. The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Eye protection: Tightly fitting safety goggles. Faceshield (8-inch minimum). Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Xylene (1330-20-7) [5-10%]

Components with workplace control parameters

TWA 100 ppm USA. Occupational Exposure Limits (OSHA) - Table Z- 1
435 mg/m3 Limits for Air Contaminants

TWA 100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
435 mg/m3 1910.1000

STEL 150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
655 mg/m3 1910.1000

TWA 100 ppm USA. ACGIH Threshold Limit Values (TLV)
434 mg/m3

Not classifiable as a human carcinogen

STEL 150 ppm USA. ACGIH Threshold Limit Values (TLV)
651 mg/m3

Not classifiable as a human carcinogen

TWA 100 ppm USA. ACGIH Threshold Limit Values (TLV)
Eye & Upper Respiratory Tract irritation Central Nervous System impairment Substances for which there is a Biological Exposure Index or Indices (see BEI section) Not classifiable as a human carcinogen

STEL 150 ppm USA. ACGIH Threshold Limit Values (TLV)
Eye & Upper Respiratory Tract irritation Central Nervous System impairment Substances for which there is a Biological Exposure Index or Indices (see BEI section) Not classifiable as a human carcinogen

Wearcoat 491 Part A

TWA 100 ppm USA. Occupational Exposure Limits (OSHA) - Table Z- 1
 435 mg/m3 Limits for Air Contaminants
 The value in mg/m3 is approximate.

TWA 100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
 435 mg/m3 1910.1000

STEL 150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants -
 655 mg/m3 1910.1000

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%] : no data available

Propanoic acid, 3-ethoxy-, ethyl ester (763-69-9) [0-1%] : no data available

Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) [16-19%] : no data available

2-Propanol, 1-methoxy-, acetate (108-65-6) [7-10%]

Components with workplace control parameters

TWA 50 ppm USA. Workplace Environmental Exposure Levels
 (WEEL)

Phenol, polymer with formaldehyde, glycidyl ether (28064-14-4) [1-5%] : no data available

9	PHYSICAL AND CHEMICAL PROPERTIES
----------	---

Appearance:	Gray	Odor:	Solvent odor
Physical State:	Viscous liquid	Solubility:	Negligible in water
Spec Grav./Density:	1.3-1.45	Percent Volatile:	30-40

10	STABILITY AND REACTIVITY
-----------	---------------------------------

Chemical Stability:	This product is stable
Conditions to Avoid:	Xylene may produce excessive pressure when heated.
Materials to Avoid:	Bases
Hazardous Decomposition:	The by products expected in complete pyrolysis or combustion of epoxy resins are mainly phenolics, carbon monoxide and water. The thermal decomposition products of epoxy resins therefore should be treated as potentially hazardous substances, and appropriate precautions should be taken.
Hazardous Polymerization:	Will not occur by itself, but masses of more than one pound of product plus an aliphatic amine can cause irreversible polymerization with considerable heat buildup.

11	TOXICOLOGICAL INFORMATION
-----------	----------------------------------

Xylene (1330-20-7) [5-10%]

Acute toxicity:
 Oral LD50 no data available
 Inhalation LC50

Wearcoat 491 Part A

Dermal LD50
Other information on acute toxicity
Skin corrosion/irritation: no data available
Serious eye damage/eye irritation: Eyes: no data available
Respiratory or skin sensitization: no data available
Germ cell mutagenicity: no data available

Carcinogenicity:
IARC: 2B - Group 2B: Possibly carcinogenic to humans (Ethylbenzene)
IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Xylene)
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available
Teratogenicity: no data available
Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available
Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available
Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%]

Acute toxicity:
Oral LD50 Oral - rat - 13,600 mg/kg Remarks: Behavioral:Somnolence (general depressed activity). Lungs, Thorax, or Respiration:Dyspnea. Nutritional and Gross Metabolic:Weight loss or decreased weight gain.
Inhalation LC50 no data available
Dermal LD50
Other information on acute toxicity
Skin corrosion/irritation: no data available
Serious eye damage/eye irritation: no data available
Respiratory or skin sensitization: May cause sensitization by skin contact.
Germ cell mutagenicity: no data available
Genotoxicity in vitro - Ames test - positive

Carcinogenicity:
IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available
Teratogenicity: no data available
Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available
Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available
Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin

Wearcoat 491 Part A

May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Propanoic acid, 3-ethoxy-, ethyl ester (763-69-9) [0-1%]

Acute toxicity:

Oral LD50 Oral - rat - male - > 5,000 mg/kg

LD50 Oral - rat - female - 4,309 mg/kg

Inhalation LC50 LC50 Inhalation - rat - male - 6 h - > 998 ppm

Dermal LD50 Dermal - rabbit - male - 4,080 mg/kg

LD50 Dermal - rabbit - female - 4,680 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation: Skin - rabbit - No skin irritation - 4 h - OECD Test Guideline 404

Serious eye damage/eye irritation: Eyes - rabbit - No eye irritation - 24 h - OECD Test Guideline 405

Respiratory or skin sensitisation: guinea pig - Does not cause skin sensitisation. - OECD Test Guideline 406

Germ cell mutagenicity: Genotoxicity in vitro - S. typhimurium - with and without metabolic activation - negative

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System):

no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed.

Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Nausea, Headache, Vomiting, Central nervous system depression, Dizziness

Additional Information:

Repeated dose toxicity - rat - male and female - Oral - No observed adverse effect level - 1,000 mg/kg RTECS: UF3325000

Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) [16-19%]

Acute toxicity:

LD50 Oral - rat - 13,000 mg/kg

Dermal: no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: Human Embryo Unscheduled DNA synthesis

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by

Wearcoat 491 Part A

OSHA.

Reproductive toxicity: no data available
Specific target organ toxicity - single exposure: Inhalation - May cause respiratory irritation.
Specific target organ toxicity - repeated exposure: no data available
To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

2-Propanol, 1-methoxy-, acetate (108-65-6) [7-10%]

Acute toxicity:
Oral LD50 Oral - rat - 8,532 mg/kg
Inhalation LC50 no data available
Dermal LD50 Dermal - rabbit - > 5,000 mg/kg
Other information on acute toxicity

Skin corrosion/irritation: Skin - rabbit - No skin irritation
Serious eye damage/eye irritation: no data available
Respiratory or skin sensitisation: Maximisation Test - guinea pig - Did not cause sensitisation on laboratory animals.
Germ cell mutagenicity: no data available

Carcinogenicity:
IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.
NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available
Teratogenicity: Specific target organ toxicity - single exposure (Globally Harmonized System):
no data available
Specific target organ toxicity - repeated exposure (Globally Harmonized System):
no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed.
Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Phenol, polymer with formaldehyde, glycidyl ether (28064-14-4) [1-5%]

Information on toxicological effects

Acute toxicity:
Oral LD50 no data available
Inhalation LC50 no data available
Dermal LD50 no data available

Other information on acute toxicity
Skin corrosion/irritation: no data available
Serious eye damage/eye irritation: no data available
Respiratory or skin sensitisation: Prolonged or repeated exposure may cause allergic reactions in certain sensitive individuals.
Germ cell mutagenicity: no data available

Carcinogenicity:
IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.
ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

Wearcoat 491 Part A

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.
OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available
Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available
Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available
Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed.
Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Synergistic effects: no data available

Additional Information:

RTECS: Not available

12

ECOLOGICAL INFORMATION

Xylene (1330-20-7) [5-10%]

Toxic to aquatic life.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%]

Persistence and degradability: Biodegradability Result: - According to the results of tests of biodegradability this product is not readily biodegradable. Remarks: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.

Propanoic acid, 3-ethoxy-, ethyl ester (763-69-9) [0-1%]

Toxicity:

Toxicity to fish static test LC50 - Pimephales promelas (fathead minnow) - 55.3 mg/l - 96 h.

Method: OECD Test Guideline 203

static test LC50 - Pimephales promelas (fathead minnow) - 45.3 mg/l - 96 h

Toxicity to daphnia Immobilization EC50 - Daphnia magna (Water flea) - > 479.7 mg/l - 48 h.

and other aquatic Method: OECD Test Guideline 202 invertebrates

Immobilization EC50 - Daphnia magna (Water flea) - 785 mg/l - 48 h

Toxicity to algae Growth inhibition EC50 - Selenastrum capricornutum (green algae) - > 114.86 mg/l - 72 h.

Method: OECD Test Guideline 201

Toxicity to bacteria Growth inhibition IC50 - other microorganisms - > 5,000 mg/l - 16 h.

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

Harmful to aquatic life.

2-Propanol, 1-methoxy-, acetate (108-65-6) [7-10%]

Toxicity:

Toxicity to fish mortality LC50 - Salmo gairdneri - 100 - 180 mg/l - 96 h.

Method: OECD Test Guideline 203

Toxicity to daphnia Immobilization EC50 - Daphnia magna (Water flea) - > 500 mg/l - 48 h.

Wearcoat 491 Part A

and other aquatic Method: Tested according to Annex V of Directive 67/548/EEC. invertebrates
Persistence and degradability: Biodegradability Biotic/Aerobic Result: 100 % - Readily biodegradable.
Other adverse effects: Biochemical Oxygen 0.36 mg/l Demand (BOD)
Chemical Oxygen 1.74 mg/g Demand (COD)
An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Harmful to aquatic life.

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%]

Information on ecological effects
Toxicity: no data available

Persistence and degradability: Biodegradability Result: - According to the results of tests of biodegradability this product is not readily biodegradable. Remarks: no data available

Bioaccumulative potential: no data available
Mobility in soil: no data available
PBT and vPvB assessment: no data available

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life with long lasting effects.
no data available

Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) [16-19%]

Information on ecological effects

Toxicity: no data available
Persistence and degradability: no data available
Bioaccumulative potential: no data available
Mobility in soil: no data available
Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Phenol, polymer with formaldehyde, glycidyl ether (28064-14-4) [1-5%]

Information on ecological effects

Toxicity: no data available
Persistence and degradability: no data available
Bioaccumulative potential: no data available
Mobility in soil: no data available
PBT and vPvB assessment: no data available

Other adverse effects: no data available

Wearcoat 491 Part A

13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product: Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material. Comply with all federal, state, and local laws concerning hazardous waste.

Contaminated packaging: Dispose of as unused product.

14 TRANSPORT INFORMATION

UN1263, Paint, 3, PGIII

IATA

UN/ID No. : UN1263

Proper shipping name :Paint

Class or Division : 3

Packing group : III

Label(s) : 3

RQ Substance : Yes

IMDG

UN/ID No. : UN1263

Proper shipping name :Paint

Class or Division : 3

Packing group : III

Label(s) : 3

RQ Substance : Yes

15 REGULATORY INFORMATION

Component (CAS#) [%] - CODES

RQ(100LBS), Xylene (1330-20-7) [5-10%] CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, SARA313, TOXICRCRA, TSCA, TXAIR, TXHWL

Phenol, 4,4'-(1-methylethylidene)bis-, polymer with (chloromethyl)oxirane (25068-38-6) [15-25%] TSCA

Propanoic acid, 3-ethoxy-, ethyl ester (763-69-9) [0-1%] TSCA

Benzene, 1-chloro-4-(trifluoromethyl)- (98-56-6) [16-19%] TSCA

2-Propanol, 1-methoxy-, acetate (108-65-6) [7-10%] TSCA

Phenol, polymer with formaldehyde, glycidyl ether (28064-14-4) [1-5%] TSCA

Regulatory CODE Descriptions

RQ = Reportable Quantity

CERCLA = Superfund clean up substance

CSWHS = Clean Water Act Hazardous substances

EPCRAWPC = EPCRA water Priority Chemicals

HAP = Hazardous Air Pollutants

MASS = MA Massachusetts Hazardous Substances List

NJHS = NJ Right-to-Know Hazardous Substances

OSHAWAC = OSHA workplace Air Contaminants

PA = PA Right-To-Know List of Hazardous Substances

SARA313 = SARA 313 Title III Toxic Chemicals

TOXICRCRA = RCRA Toxic Hazardous wastes (U-List)

TSCA = Toxic Substances Control Act

Wearcoat 491 Part A

TXAIR = TX Air Contaminants with Health Effects Screening Level
TXHWL = TX Hazardous Waste List

16

OTHER INFORMATION

Notice - This information is presented in good faith and believed to be accurate as of the effective date below. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Coatings For Industry, Inc. assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material, such vendees or users assume all risks associated with the use of the material. Regulatory requirements are subject to change and may differ from one location to another: it is the buyer's responsibility to ensure that its activities comply with federal, state, and local laws. The preceding specific information is made for the purpose of complying with numerous federal, state, and local laws and regulations