

## Wearcoat SG-LP Part A

**1 PRODUCT AND COMPANY IDENTIFICATION**

**Product Identifier:** Wearcoat SG-LP Part A  
**Common Name:** Pigmented epoxy resin  
**SDS Number:** I158  
**Revision Date:** 1/22/2019  
**Version:** 1  
**Product Use:** Epoxy floor coating  
**Supplier Details:** Coatings For Industry, Inc.  
319 Township Line Road  
Souderton, PA 18964  
**Emergency:** Infotrac  
**Contact:** USA: 1-800-535-5053 / International :352-323-3500  
**Phone:** 215-723-0919  
**Fax:** 215-723-0911  
**Email:** cs@cficoatings.com  
**Web:** www.cficoatings.com

**2 HAZARDS IDENTIFICATION****Classification of the substance or mixture****GHS Classification in accordance with 29 CFR 1910 (OSHA HCS):**

Health, Acute toxicity, 4 Dermal  
Health, Skin corrosion/irritation, 2  
Health, Serious Eye Damage/Eye Irritation, 2 B  
Health, Carcinogenicity, 1

**GHS Label elements, including precautionary statements**

**GHS Signal Word:** **DANGER**

**GHS Hazard Pictograms:**

**GHS Hazard Statements:**

H312 - Harmful in contact with skin  
H315 - Causes skin irritation  
H320 - Causes eye irritation  
H350 - May cause cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)

**GHS Precautionary Statements:**

P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P273 - Avoid release to the environment.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P301+312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.  
P302+352 - IF ON SKIN: Wash with soap and water.  
P312 - Call a POISON CENTER or doctor/physician if you feel unwell.  
P330 - Rinse mouth.  
P332+313 - If skin irritation occurs: Get medical advice/attention.  
P362 - Take off contaminated clothing and wash before reuse.  
P501 - Dispose of contents/container in compliance with all Federal, State/Provincial and local laws

**Hazards not otherwise classified (HNOC) or not covered by GHS**

## Wearcoat SG-LP Part A

**Route of Entry:** Skin contact, and Eye contact.

**Target Organs:** Eyes, skin , respiratory system.

Chronic (Cancer) Information:

Contains CRYSTALLINE SILICA, which can be a health hazard. Respirable crystalline silica can cause the occupational lung disease silicosis (a scarring of the lungs), and IARC concluded in October 1996 that crystalline silica is carcinogenic to humans. Silicosis increases the risk of tuberculosis, autoimmune and chronic kidney diseases, as well as non-malignant respiratory disease (such as chronic bronchitis and emphysema).

IARC: A component of this product present at levels greater than or equal to 0.1% is identified as a probable, possible or confirmed human carcinogen by IARC.

ACGIH: A component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP: A component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Inhalation:** The low vapor pressure of the resin makes inhalation unlikely in normal use.

**Skin Contact:** - Moderate irritant. Contact at elevated temperatures can cause thermal burns. May cause skin sensitization (rashes, hives). Prolonged skin contact is unlikely to result in absorption of harmful amounts.

**Eye Contact:** Moderate to severe irritant. Contact at elevated temperatures can cause thermal burns.

**3 COMPOSITION/INFORMATION ON INGREDIENTS****Ingredients:**

Cas#	%	Chemical Name
14808-60-7	56-60%	Silica, crystalline quartz
107-98-2	2-5%	1-Methoxy-2-propanol
13463-67-7	1-5%	Titanium dioxide
100-51-6	0.5-2%	Benzyl alcohol

**4 FIRST AID MEASURES**

**Inhalation:** If affected, remove to fresh air.

If not breathing, give artificial respiration.

Call a physician if symptoms develop or persist.

**Skin Contact:** Wash with soap and water. Remove contaminated clothing and footwear immediately, and wash before reuse. Discard clothing and footwear which cannot be decontaminated. Get medical attention if symptoms occur.

**Eye Contact:** Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation.

Then remove contact lenses, if easily removeable, and continue irrigation for not less than 15 minutes.

**Ingestion:** Ensure adequate flushing of the eyes by separating the eyelids with fingers and roll eyes in a circular motion. DO NOT induce vomiting. If vomiting does occur, have victim lean forward to prevent aspiration. Rinse mouth with water. Seek medical attention. Never give anything by mouth to an unconscious individual.

**5 FIRE FIGHTING MEASURES**

**Flash Point:** Greater than 200F

**LEL:** 6.0

**UEL:** 18.8

## Wearcoat SG-LP Part A

Hazardous gases/vapors produced in fire are carbon monoxide, carbon dioxide, phenolics.

Extinguishing Media: Waterbased material will not burn until all water has boiled away. Residual solids and/or product container may support combustion. Use water, foam, dry chemical or CO<sub>2</sub>.

## Fire Fighting Instructions:

Full emergency equipment with self-contained breathing apparatus and full protective clothing should be worn by fire fighters. During a fire irritating, highly toxic gases may be generated by thermal decomposition or combustion. (See Section VIII) Emits toxic fumes under fire conditions. Isolate from heat, electrical equipment, sparks, and open flame. Closed container may explode when exposed to extreme heat. Wear neoprene gloves when handling refuse from fire.

6

**ACCIDENTAL RELEASE MEASURES****Containment Techniques**

Contain spill.

**Clean-Up Techniques**

Wear proper personal protective clothing and equipment.

Do not flush liquid into public sewer, water systems or surface waters.

Soak up large spill residue and small spills with an inert absorbent. Place into labeled, closed container; store in safe location to await disposal. Wash the spill area with soap and water. Dispose of in accordance with national and local regulations.

Change contaminated clothing and launder before reuse.

CAUTION: Spilled liquid and dried film may be slippery. Use care to avoid falls.

7

**HANDLING AND STORAGE****Handling Precautions:**

Avoid eye contact.

Avoid repeated or prolonged skin contact.

Avoid inhalation of aerosol, mist, spray, fume or vapor.

Avoid drinking, tasting, swallowing or ingesting this product.

Wash thoroughly after handling this product. Always wash up before eating, smoking or using the facilities.

Provide eyewash fountains and safety showers in the work area.

Use under well ventilated conditions.

**Storage Requirements:**

Do not store in open, unlabeled or mislabeled containers.

Do not allow product to freeze.

Do not puncture or stack drums.

Keep container closed when not in use.

Do not reuse empty container without commercial cleaning or reconditioning.

8

**EXPOSURE CONTROLS/PERSONAL PROTECTION****Engineering Controls:**

Always provide effective general and, when necessary, local exhaust ventilation to draw spray, aerosol, fume, mist and vapor away from workers to prevent routine inhalation. Ventilation must be adequate to maintain the ambient workplace atmosphere below the exposure limit(s) outlined in the MSDS.

Ventilation guidelines/techniques may be found in publications such as Industrial Ventilation: American Conference of Governmental Industrial Hygienists, 1330 Kemper Meadow Drive, Cincinnati, OH, 45240 1634, USA.

**Personal Protective Equipment:**

Benzyl alcohol (100-51-6)

Personal protective equipment

Eye/face protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

---

## Wearcoat SG-LP Part A

---

Full contact: Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min  
Material tested: Butoject (KCL 897 / Aldrich Z677647, Size M)

Splash contact: Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 30 min  
Material tested: Camatril (KCL 730 / Aldrich Z677442, Size M) data source: KCL GmbH, D-36124  
Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or  
mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the  
CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial  
hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It  
should not be construed as offering an approval for any specific use scenario.

Body Protection: Complete suit protecting against chemicals, The type of protective equipment must be  
selected according to the concentration and amount of the dangerous substance at the specific  
workplace.

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a  
full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges  
as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face  
supplied air respirator. Use respirators and components tested and approved under appropriate  
government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure: Prevent further leakage or spillage if safe to do so. Do not let  
product enter drains. Discharge into the environment must be avoided.

Silica, crystalline quartz (14808-60-7)

Personal protective equipment

Respiratory protection: For nuisance exposures use type P95 (US) or type P1 (EU EN 143) particle  
respirator. For higher level protection use type OV/AG/P99 (US) or type ABEK-P2 (EU EN 143) respirator  
cartridges. Use respirators and components tested and approved under appropriate government  
standards such as NIOSH (US) or CEN (EU).

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal  
technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of  
contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash  
and dry hands.

Eye protection: Safety glasses with side-shields conforming to EN166 Use equipment for eye protection  
tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection: Complete suit protecting against chemicals, The type of protective equipment  
must be selected according to the concentration and amount of the dangerous substance at the specific  
workplace.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands  
before breaks and at the end of workday.

### Benzyl alcohol (100-51-6)

Components with workplace control parameters

TWA	10 ppm	USA. Workplace Environmental Exposure Levels (WEEL)
-----	--------	--

### Silica, crystalline quartz (14808-60-7)

Components with workplace control parameters

## Wearcoat SG-LP Part A

TWA 0.025 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  
Suspected human carcinogen

TWA 0.025 mg/m3 USA. ACGIH Threshold Limit Values (TLV)  
Lung cancer Pulmonary fibrosis Suspected human carcinogen

### Titanium Dioxide (13463-67-7)

TWA 15mg/m3 8hr. OSHA/PEL

### 1-Methoxy-2-propanol (107-98-2)

TWA 100 ppm USA. ACGIH Threshold Limit Values (TLV)  
Central Nervous System impairment  
Eye irritation

STEL 150 ppm USA. ACGIH Threshold Limit Values (TLV)  
Central Nervous System impairment  
Eye irritation

TWA 100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
360 mg/m3

STEL 150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
540 mg/m3

TWA 100 ppm USA. NIOSH Recommended Exposure Limits  
360 mg/m3

STEL 150 ppm USA. NIOSH Recommended Exposure Limits  
540 mg/m3

### Titanium Dioxide (13463-67-7)

Permissible exposure limit:  
(OSHA): 15 mg/m3 8 hr. TWA Total dust.  
TLV (ACGIH): 10 mg/m3 TWA

9	PHYSICAL AND CHEMICAL PROPERTIES		
<b>Appearance:</b> <b>Physical State:</b> <b>Spec Grav./Density:</b> <b>Boiling Point:</b> <b>pH:</b>	Opaque Liquid 1.605 212 F 8-10	<b>Odor:</b> <b>Freezing/Melting Pt.:</b> <b>VOC:</b>	slight odor 32 F Part A: 0.57 lb./gal. ; Mixed Coating: 0.83

## Wearcoat SG-LP Part A

10

**STABILITY AND REACTIVITY**

<b>Chemical Stability:</b>	This product is stable
<b>Conditions to Avoid:</b>	Heating above 300 ° F in the presence of air may cause slow oxidation decomposition and above 662 ° F may cause potentially violent decomposition.
<b>Materials to Avoid:</b>	Strong oxidizers, acids, bases, and epoxy hardeners under uncontrolled conditions.
<b>Hazardous Decomposition:</b>	Decomposition or combustion may generate irritating vapors, CO, CO <sub>2</sub> , Phenolics.
<b>Hazardous Polymerization:</b>	Hazardous polymerization will not occur.

11

**TOXICOLOGICAL INFORMATION****Benzyl alcohol (100-51-6)**

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 1,230 mg/kg Remarks: Behavioral:Somnolence (general depressed activity). Behavioral:Excitement. Behavioral:Coma.

Inhalation: no data available

LD50 Dermal - rabbit - 2,000 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: Irritating to skin. - 24 h

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information:

RTECS: DN3150000

Central nervous system depression

Liver - Irregularities - Based on Human Evidence

**Silica, crystalline quartz (14808-60-7)**

Information on toxicological effects

Acute toxicity:

Oral LD50 LD50: >5000 mg/kg, rat. Category 5

---

## Wearcoat SG-LP Part A

---

Inhalation LC50  
Dermal LD50  
Other information on acute toxicity  
Skin corrosion/irritation: no data available  
Serious eye damage/eye irritation: no data available  
Respiratory or skin sensitization: no data available

Germ cell mutagenicity: no data available

### Carcinogenicity:

Limited evidence of carcinogenicity in human studies

IARC: 1 - Group 1: Carcinogenic to humans (Quartz)

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: Known to be human carcinogen (Quartz)

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System): no data available

Specific target organ toxicity - repeated exposure (Globally Harmonized System): Inhalation - May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. May cause respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. May cause skin irritation. Eyes May cause eye irritation.

Signs and Symptoms of Exposure: Prolonged inhalation of crystalline silica may result in silicosis, a disabling pulmonary fibrosis characterized by fibrotic changes and miliary nodules in the lungs, a dry cough, shortness of breath, emphysema, decreased chest expansion, and increased susceptibility to tuberculosis. In advanced stages, loss of appetite, pleuritic pain, and total incapacity to work. Advanced silicosis may result in death due to cardiac failure or destruction of lung tissue. Crystalline silica is classified as group 1 "known to be carcinogenic to humans" by IARC and "sufficient evidence" of carcinogenicity by the NTP. The chronic health risks are associated with respirable particles of 3-4 um over protracted periods of time. Currently, there is a limited understanding of the mechanisms of quartz toxicity, including its mechanisms for lung carcinogenicity. Additional studies are needed to determine whether the cell transforming activity of quartz is related to its carcinogenic potential.

Synergistic effects: no data available

### Additional Information:

RTECS: VV7330000

### 1-Methoxy-2-propanol (107-98-2)

#### Information on toxicological effects

##### Acute toxicity:

LD50 Oral - mouse - 11,700 mg/kg Remarks: Behavioral:Convulsions or effect on seizure threshold. Behavioral:Ataxia. Lungs, Thorax, or Respiration:Dyspnea.

LC50 Inhalation - rat - 5 h - 10000 ppm

LD50 Dermal - rabbit - 13,000 mg/kg

Skin corrosion/irritation: Skin - rabbit Result: Open irritation test

Serious eye damage/eye irritation: Eyes - rabbit Result: Mild eye irritation - 24 h

Respiratory or skin sensitisation: no data available



---

## Wearcoat SG-LP Part A

---

Germ cell mutagenicity: no data available

**Carcinogenicity:**

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

**Additional Information:**

RTECS: UB7700000

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence

Stomach - Irregularities - Based on Human Evidence

**Titanium Dioxide (13463-67-7)**

Inhalation 4 h LC50 : > 6.82 mg/l , Rat

Dermal LD50 : > 10,000 mg/kg , Rabbit

Oral LD50 : > 5,000 mg/kg , Rat

Skin irritation : Slight or no skin irritation, Rabbit

Eye irritation : Slight or no eye irritation, Rabbit

Sensitisation : Did not cause sensitisation on laboratory animals., Mouse

Did not cause sensitisation on laboratory animals., Guinea pig

Repeated dose toxicity : Oral (Rat): No toxicologically significant effects were found.

Inhalation (Rat): No toxicologically significant effects were found.

**Carcinogenicity:**

IARC: Group 2B: "possibly carcinogenic to humans".

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by

ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by

NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by

OSHA.

Mutagenicity : Did not cause genetic damage in animals.

Tests on bacterial or mammalian cell cultures did not show mutageniceffects.



## Wearcoat SG-LP Part A

12

**ECOLOGICAL INFORMATION****Benzyl alcohol (100-51-6)**

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - *Lepomis macrochirus* (Bluegill) - 10 mg/l - 96 h.

Toxicity to daphnia and EC50 - *Daphnia magna* (Water flea) - 55 mg/l - 24 h.  
other aquatic invertebrates

Persistence and degradability: Biodegradability Biotic/Aerobic - Exposure time 28 d Result: 92 - 96 % - Readily biodegradable.

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Toxic to aquatic life.

**Silica, amorphous (7631-86-9)**

Information on ecological effects

Toxicity: LC50 (96h) (static) 10000 mg/l (zebra fish) (OECD 203)

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted.

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.  
Harmful to aquatic life with long lasting effects.

**Titanium Dioxide (13463-67-7)**

Aquatic Toxicity

96 h LC50: *Pimephales promelas* (fathead minnow) > 1,000 mg/l

72 h EC50 : *Pseudokirchneriella subcapitata* (green algae) 61 mg/l

48 h EC50: *Daphnia magna* (Water flea) > 1,000 mg/l

Environmental Fate

Biodegradability : Pigments are practically not biodegradable.

Bioaccumulation : Does not bioaccumulate.

13

**DISPOSAL CONSIDERATIONS**

Dispose of in accordance with local, state, and federal regulations. Incineration is the preferred method.

14

**TRANSPORT INFORMATION**

This product is not regulated for ground or air transportation.

## Wearcoat SG-LP Part A

15

**REGULATORY INFORMATION**

Component (CAS#) [%] - CODES

-----  
Silica, crystalline quartz (14808-60-7) [56-60%] GADSL, MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

1-Methoxy-2-propanol (107-98-2) [2-5%] HAP, MASS, OSHAWAC, PA, TSCA, TXAIR

Titanium dioxide (13463-67-7) [1-5%] MASS, OSHAWAC, PA, TSCA, TXAIR

Benzyl alcohol (100-51-6) [0.5-2%] HAP, MASS, PA, TSCA

Regulatory CODE Descriptions

-----  
GADSL = Global Automotive Declarable Substance List (GADSL)  
MASS = MA Massachusetts Hazardous Substances List  
NRC = Nationally Recognized Carcinogens  
OSHAWAC = OSHA Workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
TSCA = Toxic Substances Control Act  
TXAIR = TX Air Contaminants with Health Effects Screening Level  
HAP = Hazardous Air Pollutants

16

**OTHER INFORMATION**

**NOTICE:** This information is presented in good faith and believed to be accurate as of the effective date below. However, no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. Coatings For Industry, Inc. assumes no responsibility for personal injury or property damage to vendees, users, or third parties caused by the material. Such vendees or users assume all risks associated with the use of the material. Regulatory requirements are subject to change and may differ from one location to another: it is the buyer's responsibility to ensure that its activities comply with federal, state or provincial, and local laws. The preceding specific information is made for the purpose of complying with numerous federal, state or provincial, and local laws and regulations.